

Foundations GlueDown offers a practical, easy-to-replace flooring solution ideal for budget-conscious projects. Coordinated visuals make it simple to maintain a cohesive look across multiple installation methods.

SPECIFICATIONS

Product Type	Luxury Vinyl Plank (LVP)
Core Material	1.6mm Virgin Vinyl
Fiberglass Reinforced	FiberBlend
Overall Thickness	1.6mm (0.063")
Nominal Plank Size	7" x 48"
Actual Plank Size	177.8mm x 1219.2mm
Wear Layer	6mil ScratchGuard
Embossing	Natural Wood Texture
Visual	Premium Wood Visual
Surface Protection	Enhanced Polyurethane System
Installation Type	GlueDown
Bacteria Resistance	Standard
Edge Profile	Square Edge
Temperature Range	60° F - 95° F
Acclimation Time	48hr Acclimation Required
Radiant Heat Compatible	Yes
Recommended Adhesive	3010 Prism, 3020 Everlast, or 3050 Omni

WARRANTY

Residential	10 Years
Light Commercial	3 Years
Heavy Commercial	None

PACKAGING

Carton:		Pallet:		Truckload:		Container:	
Pieces	28	Cartons	55	Pallets	18	Pallets	20
Square Feet	65.40 sqft	Square Feet	3597 sqft	Cartons	990	Cartons	1,100
Square Meters	6.07 m2	Square Meters	333.85 m2	Square Feet	64746 sqft	Square Feet	71940 sqft
Weight	41.09 lbs	Weight	2293.25 lbs	Square Meters	6009.3 m2	Square Meters	6677 m2
Weight (kg)	18.64 kg	Weight (kg)	1040.2 kg			Weight	45864.91 lbs
						Weight (kg)	20804 kg

RUNNING LINE SKUS

1101	Mission Bay	1103	Sonora Heights 	1104	Newport Landing	1105	Hansen Creek
1106	Rochester Springs	1108	Longview Point				

SPECIAL ORDER SKUS

1102	Carvins Cove	1107	Balboa Trails
------	--------------	------	---------------



Signature
DESIGN

Urban Surfaces' **Signature Collection** features our most sought-after flooring designs, carefully selected from across our diverse lines.

Choosing from the Signature Collection means investing in flooring that has proven its timeless appeal through unmatched durability and enduring style.

MANUFACTURING & USAGE TESTING

Standards:	Descriptions:	Requirements:	Test Results:
ASTM F925	Chemical Resistance	No More Than Slight Change	Passes
ASTM F1515	Light Resistance	< 8.0 Delta E	Passes
ASTM F1514	Heat Resistance	< 8.0 Delta E	Passes

SAFETY & PERFORMANCE TESTING


Standards:	Descriptions:	Requirements:	Test Results:
ASTM D2047	Slip Resistance	≥ 0.5	>0.58 (Dry)
ASTM F970	Static Load		2,000 PSI .005 in
ASTM E648	Radiant Flux	Class 1 ≥ 0.45 W/cm ²	Class 1
ASTM E662	Smoke Density	Dmc ≤ 450	Passes
CPSC-CH-C1001-09.4	Phthalates	≤ 0.1% (CPSIA)	Passes
CPSC-CH-E1002-08.3	Heavy Metals	Below CPSIA / F963 Limits	Passes
ASTM D6007	Formaldehyde	Meets CARB II	Passes
California 01350	FloorScore Certified	Meets CDPH v1.2	Passes

CONTRIBUTIONS TOWARDS LEED CERTIFICATION

Category:	Credit:	Contribution:
Indoor Environmental Quality	EQ Credit: Low-Emitting Materials	1 Point
Materials & Resources	MR Credit: Building Product Disclosure and Optimization - Environmental Product Declarations	1 Point

INSTALLATION

End Use:	Suitable Grade Level:	Installation Method:	Installation Sundries As Required:
Residential	All grades where excessive moisture conditions do not exist	Glue Down	3010 Prism, 3020 Everlast, 3050 Omni, Infiniti Moisture Barrier



BIM Files and more available at <https://www.urbansurfaces.com/bim/>

CERTIFICATIONS

