

Main Street offers a clean, natural wood look tailored for multifamily and residential spaces. It balances everyday durability with easy maintenance, making it a dependable choice for high-turn environments.

SPECIFICATIONS

Product Type	Luxury Vinyl Plank (LVP)
Core Material	2mm Virgin Vinyl
Fiberglass Reinforced	FiberBlend
Overall Thickness	2mm (0.079")
Nominal Plank Size	7" x 48"
Actual Plank Size	177.8mm x 1219.2mm
Wear Layer	8mil ScratchGuard
Embossing	Natural Wood Texture
Visual	Premium Wood Visual
Surface Protection	Enhanced Polyurethane System
Installation Type	GlueDown
Bacteria Resistance	Standard
Edge Profile	Square Edge
Temperature Range	60° F - 95° F
Acclimation Time	48hr Acclimation Required
Radiant Heat Compatible	Yes
Recommended Adhesive	3010 Prism, 3020 Everlast, or 3050 Omni

WARRANTY

Residential	15 Years
Light Commercial	5 Years
Heavy Commercial	None

PACKAGING

Carton:		Pallet:		Truckload:		Container:	
Pieces	22	Cartons	50	Pallets	20	Pallets	20
Square Feet	51.39 sqft	Square Feet	2569.5 sqft	Cartons	1,000	Cartons	1,000
Square Meters	4.77 m2	Square Meters	238.5 m2	Square Feet	51390 sqft	Square Feet	51390 sqft
Weight	39.02 lbs	Weight	1984.16 lbs	Square Meters	4770 m2	Square Meters	4770 m2
Weight (kg)	17.70 kg	Weight (kg)	900 kg			Weight	39683.16 lbs
						Weight (kg)	18000 kg

RUNNING LINE SKUS

8050	Midland Grey	8061	Marquette 	8070	Aspen	8071	Hudson
8123	Briscoe 	8307	Ash				

SPECIAL ORDER SKUS

8051	Twilight	8060	Sierra	8122	Barn Owl	8306	Presidio
------	----------	------	--------	------	----------	------	----------



Urban Surfaces' **Signature Collection** features our most sought-after flooring designs, carefully selected from across our diverse lines.

Choosing from the Signature Collection means investing in flooring that has proven its timeless appeal through unmatched durability and enduring style.

MANUFACTURING & USAGE TESTING

Standards:	Descriptions:	Requirements:	Test Results:
ASTM F925	Chemical Resistance	No More Than Slight Change	Passes
ASTM F1515	Light Resistance	< 8.0 Delta E	Passes
ASTM F1514	Heat Resistance	< 8.0 Delta E	Passes

SAFETY & PERFORMANCE TESTING


Standards:	Descriptions:	Requirements:	Test Results:
ASTM D2047	Slip Resistance	≥ 0.5	>0.58 (Dry)
ASTM F970	Static Load		2,000 PSI .005 in
ASTM E648	Radiant Flux	Class 1 ≥ 0.45 W/cm ²	Class 1
ASTM E662	Smoke Density	Dmc ≤ 450	Passes
CPSC-CH-C1001-09.4	Phthalates	≤ 0.1% (CPSIA)	Passes
CPSC-CH-E1002-08.3	Heavy Metals	Below CPSIA / F963 Limits	Passes
ASTM D6007	Formaldehyde	Meets CARB II	Passes
California 01350	FloorScore Certified	Meets CDPH v1.2	Passes

CONTRIBUTIONS TOWARDS LEED CERTIFICATION

Category:	Credit:	Contribution:
Indoor Environmental Quality	EQ Credit: Low-Emitting Materials	1 Point
Materials & Resources	MR Credit: Building Product Disclosure and Optimization - Environmental Product Declarations	1 Point

INSTALLATION

End Use:	Suitable Grade Level:	Installation Method:	Installation Sundries As Required:
Residential, Light Commercial	All grades where excessive moisture conditions do not exist	Glue Down	3010 Prism, 3020 Everlast, 3050 Omni, Infiniti Moisture Barrier



BIM Files and more available at <https://www.urbansurfaces.com/bim/>

CERTIFICATIONS

