

SoHo Square is designed for statement-making commercial spaces. With elevated visuals and heavy-duty performance, it delivers long-term durability while giving designers a floor that looks as intentional as it performs.

SPECIFICATIONS

Product Type	Luxury Vinyl Plank (LVP)
Core Material	3mm Virgin Vinyl
Fiberglass Reinforced	FiberBlend
Overall Thickness	3mm (0.118")
Nominal Plank Size	7" x 48"
Actual Plank Size	177.8mm x 1219.2mm
Wear Layer	20mil ScratchGuard
Embossing	Natural Wood Texture
Visual	Premium Wood Visual
Surface Protection	Enhanced Polyurethane System
Installation Type	GlueDown
Bacteria Resistance	Standard
Edge Profile	Square Edge
Temperature Range	60° F - 95° F
Acclimation Time	48hr Acclimation Required
Radiant Heat Compatible	Yes
Recommended Adhesive	3010 Prism, 3020 Everlast, or 3050 Omni

WARRANTY

Residential	Lifetime
Light Commercial	20 Years
Heavy Commercial	15 Years

PACKAGING

Carton:		Pallet:		Truckload:		Container:	
Pieces	15	Cartons	55	Pallets	18	Pallets	20
Square Feet	35.00 sqft	Square Feet	1925 sqft	Cartons	990	Cartons	1,100
Square Meters	3.25 m2	Square Meters	178.75 m2	Square Feet	34650 sqft	Square Feet	38500 sqft
Weight	40.12 lbs	Weight	2239.95 lbs	Square Meters	3217.5 m2	Square Meters	3575 m2
Weight (kg)	18.20 kg	Weight (kg)	1016.03 kg			Weight	44799.08 lbs
						Weight (kg)	20320.55 kg

RUNNING LINE SKUS

7501 Canal Street	7502 Sullivan Street	7503 Boardwalk	7504 Waverly Place
7505 Wooster Street	7507 Crosby Street	7508 Sedona Bridge 	7509 Dakota Way
7524 West Broadway	7526 Charlton Plaza	7527 Sixth Avenue	7528 Courtland Alley



Urban Surfaces' **Signature Collection** features our most sought-after flooring designs, carefully selected from across our diverse lines.

Choosing from the Signature Collection means investing in flooring that has proven its timeless appeal through unmatched durability and enduring style.

SOUND TESTING

SOHO SQUARE 3mm GlueDown	+ FloorSilencerPro Underlayment Roll					
	HIIC	LIIC	IIC	ΔHIIC	ΔIIC	STC
on Wood Assembly	63	40	55	-	-	58
on 6" Concrete Slab	58	65	57	27	23	53
on 6" Concrete Slab with Insulation and Drywall	70	68	67	-	-	61
on 8" Concrete Slab	59	70	57	-	-	55

SOUND TESTING STANDARDS

HIIC: ASTM E3222	LIIC: ASTM E3207	IIC: ASTM E492	STC: ASTM E90
----------------------------	----------------------------	--------------------------	-------------------------

MANUFACTURING & USAGE TESTING

Standards:	Descriptions:	Requirements:	Test Results:
ASTM F925	Chemical Resistance	No More Than Slight Change	Passes
ASTM F1515	Light Resistance	< 8.0 Delta E	Passes
ASTM F1514	Heat Resistance	< 8.0 Delta E	Passes

SAFETY & PERFORMANCE TESTING


Standards:	Descriptions:	Requirements:	Test Results:
ASTM D2047	Slip Resistance	≥ 0.5	>0.58 (Dry)
ASTM F970	Static Load		2,000 PSI .005 Inch
ASTM E648	Radiant Flux	Class 1 ≥ 0.45 W/cm ²	Class 1
ASTM E662	Smoke Density	Dmc ≤ 450	Passes
CPSC-CH-C1001-09.4	Phthalates	≤ 0.1% (CPSIA)	Passes
CPSC-CH-E1002-08.3	Heavy Metals	Below CPSIA / F963 Limits	Passes
ASTM D6007	Formaldehyde	Meets CARB II	Passes
California 01350	FloorScore Certified	Meets CDPH v1.2	Passes

CONTRIBUTIONS TOWARDS LEED CERTIFICATION

Category:	Credit:	Contribution:
Indoor Environmental Quality	EQ Credit: Low-Emitting Materials	1 Point
Materials & Resources	MR Credit: Building Product Disclosure and Optimization - Environmental Product Declarations	1 Point

INSTALLATION

End Use:	Suitable Grade Level:	Installation Method:	Installation Sundries As Required:
Residential, Light Commercial, Commercial	All grades where excessive moisture conditions do not exist	Glue Down	3010 Prism, 3020 Everlast, 3050 Omni, Infiniti Moisture Barrier



BIM Files and more available at <https://www.urbansurfaces.com/bim/>

CERTIFICATIONS

